



# Hotpoint® PTAC with Electric Heat 12,000 BTU, 230/208V, 20amp Model# AHES12D3XXA

| = | <br> | _ | _ | _ |   | and the set of the set |  |
|---|------|---|---|---|---|------------------------|--|
|   |      |   |   |   |   |                        |  |
| - | <br> |   |   |   |   |                        |  |
| - | <br> |   |   |   |   |                        |  |
| - | <br> |   |   |   |   |                        |  |
| - | <br> |   |   |   |   |                        |  |
| - | <br> |   |   |   |   |                        |  |
| - | <br> |   |   |   |   |                        |  |
| - | <br> |   |   |   |   |                        |  |
| _ |      |   |   |   |   |                        |  |
| _ | <br> |   |   |   |   |                        |  |
|   | <br> |   |   | - |   |                        |  |
| - | <br> | - | - | - | - |                        |  |
|   | <br> |   |   |   | - |                        |  |

- 2 Fan Speeds
- 4 Temperature-Limiting Options
- Auto Dimming Display
- Slinger Ring Condensate Removal
- Coverless Control Panel
- Automatic Emergency Heat
- Freeze/Frost & Overheat Protection
- Auto Power Recovery
- Self-Diagnostics
- Constant Fan Button

Have more questions? Please contact 1-800-626-2000

| FEATURES               |   |  |  |  |  |  |  |  |
|------------------------|---|--|--|--|--|--|--|--|
| Control Type           | Electronic  |  |  |  |  |  |  |  |
| Fan Speed Selections   | 3 Cooling<br>3 Fan Only<br>3 Heating  |  |  |  |  |  |  |  |
| Discharge Grille       | 2-position  |  |  |  |  |  |  |  |
| Product Type           | Packaged Terminal Air Conditioners (PTAC)   |  |  |  |  |  |  |  |
| Refrigerant Type       | R32   |  |  |  |  |  |  |  |
| Manual Vent Control    | Hidden  |  |  |  |  |  |  |  |
| "SmartFan" Fan Cycle   | Yes   |  |  |  |  |  |  |  |
| Chassis Type           | Slide-In  |  |  |  |  |  |  |  |
| Fan Motor              | 2   |  |  |  |  |  |  |  |
| Unit Features          | Auto Power Recovery<br>Automatic Indoor Frost Control<br>Central Desk Control Compatibility<br>Freeze Sentinel<br>Power Cord (LCDI) included<br>Remote Thermostat Compatibility |  |  |  |  |  |  |  |
| Temperature Range      | 62 - 80 F   |  |  |  |  |  |  |  |
| Heat - Cool            | Yes   |  |  |  |  |  |  |  |
| Auto Power Recovery    | Yes   |  |  |  |  |  |  |  |
| Rotary Compressor      | Yes   |  |  |  |  |  |  |  |
| Outdoor Vent / Exhaust | Yes   |  |  |  |  |  |  |  |
| Venting Features       | Concealed Manual Vent Control Vent Air Filter   |  |  |  |  |  |  |  |
| Heating System         | Electric Resistance   |  |  |  |  |  |  |  |



# Hotpoint® PTAC with Electric Heat 12,000 BTU, 230/208V, 20amp Model# AHES12D3XXA

### APPROXIMATE DIMENSIONS(HxDxW)

• 16 H x 42.40 W x 20.90 D

### CAPACITY

- Cooling BTUH (MAX) 12400.00Btu
- Cooling EER (BTUH / Watt) 10.4/10.5
- Cooling BTUH (MIN) 12200Btu

#### APPEARANCE

- Installation Through-the-Wall
- Color Appearance White

#### **WEIGHTS & DIMENSIONS**

- Overall Width (in) 42 2/5in
- Approximate Shipping Weight (lb) 102 1/10lb
- Overall Height (in) 16in
- Overall Depth (in) 20 9/10in
- Net Weight (lb) 92lb

#### **POWER / RATINGS**

- Cooling Amperes 6.1/5.8
- Cooling Watts 1190/1160
- Voltage (MIN) 208V
- Heating Electric Heater Watts 3500
- Voltage (MAX) 230.00000V

#### WARRANTY

- · Warranty Notes See written warranty for full details
- Labor Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system
- Parts Warranty Limited 1-year entire appliance Limited 5-year sealed refrigerating system

#### CERTIFICATIONS

- Claims & Certifications AHRI CSA CUL UL
  - NRCAN

Have more questions? Please contact 1-800-626-2000